

## HERCULES HOISTS LIMITED




## **Chain Pulley Block**

Triple Spur Gear

**Indef - C Series** 

- Lifting
- Moving
- Storing



- ► Capacity Range 1T, 2T, 3T, 5T, 8T, 10T, 16T & 20T
- ► CE & ISI Certified Chain Pulley Blocks
  Assured quality
- ► Made in INDIA design with optimal operating pull Assured reliability
- ► Double chain Guide Rollers

  Accurate alignment of load chain
- Pocketed alloy steel load chain wheel Extended chain life
- Case hardened gears Extended working life
- Use of needle roller bearingsHigh operating efficiency
- ► Smooth passage of load chain Unique cover design
- Self sustaining maintenance free friction brake Reduced downtime
- ► Grade 80 load chain for strength & wear resistance Longer chain life
- Anti corrosive powder coated finish cover & zinc plated parts

Better aesthetics

- ► Lifelong lubrication

  Minimal maintenance required
- Light weight and sturdy
  Ease of handling
- Forged free swivelling upper & lower hook block with safety latch
   Higher grade safety

Optional • Ex/ Atex / Spark proof design


# Material Handling. Delivered


Redefining Material Handling. Since 1962.





# www.indef.com






CAPACITY(T)	MT	1T	2T	3T	5T	8T	10T
Number of falls of load chain	Nos.	1	2	1	2	3	4
Load Chain size Dia.	mm	6.3	6.3	10	10	10	10
Hand Chain size Dia.	mm	5	5	5	5	5	5
A Hook suspension	mm	380	450	535	805	830	850
with trolley, range1&2	mm	430	500	705	895	980	880
with trolley, range3	mm	470	540	720	895	980	880
В	mm	161	161	228	280	430	480
С	mm	130	130	175	209	220	220
Н	mm	31	32	42	51	75	75
Weight at 3 M Lift	Kg.	10	11	20	59	94	130
• Extra weight per additional M lift	Kg.	1.8	2.6	3.0	5.7	7.9	10.1
<ul> <li>Running pull on hand chain</li> </ul>	Kg.	25	28	34	41	46	43
<ul><li>Velocity ratio</li></ul>		45	90	78	156	234	312

Data tolerance ±10%

 $Note: \hbox{-} \ Due \ to \ continuous \ development \ and \ improvement \ specification \ listed \ above \ may \ be \ changed \ without \ notice.$ 



HERCULES HOISTS LIMITED
43/2B, Savroli-Kharpada Road, Dhamani, Khalapur - 410 202, Maharashtra, India
Regional offices: Chennai | Kolkata | New Delhi | Pune
Tel :+91 (0)2192 662511 | Fax: +91 (0) 2192 662504
www.indef.com | enquire@indef.com

